

# Undersink Mixer Tap Ultra Violet System

GT7-4UVG

**Suits:** For use with GT1-3MK with 3/4" ports  
Twin Undersink Filtration Systems



This UV is ideal for under sink sterilisation where the home owner wishes to use the filtration and UV system via the mixer or the existing cold water tap on the sink.

## Features Include:

**Commercial Grade Stainless Steel: 316 Construction**  
**Fitted with visual and audible Lamp Fail Alarms**  
**Includes Brackets for easy installation onto undersink filtration system**

## Specs:

**Flow: Ltrs/Min:** 33 LPM

**Lamp:** 30 watt

**Product Dimensions:** 130mm vessel width, 590mm Length, 65mm height

**Quartz Thimble:** 22mm Outer Diameter, 540mm Length

**Port:** 3/4"

**Warranty:** 12 Months

## Benefits of UV

- \* Economical and efficient
- \* No harmful by-products
- \* Environmentally friendly
- \* No risk of overdosing
- \* Proven performance
- \* Easy maintenance

The ultraviolet germicidal system has become an exceptionally popular water disinfection alternative. No micro-organism is known to be immune to UV. Heavy duty UV lamps and quartz thimble using highest grade "hard glass" pure fused quartz to allow highest output

Modern technology is incorporated to create the most natural purification. Ultraviolet lamps produce germicidal short wave radiation, which eradicates bacteria, viruses and other kinds of microbiological contamination present in all water supplies.

**These are recommended levels, for use as a guideline for pre-treatment requirements:**

Hardness: <120ppm

Turbidity: <1.0NTU

Iron: <0.3ppm

Manganese: <0.05ppm

Tannins: <0.1ppm

If your water quality parameters do not meet these criteria, please contact the distributor for pre-treatment recommendations.